

Cedro

SAUNA™

Cold Plunge Manual

This manual outlines setup, use, and care.

We hope you will enjoy your Cedro Sauna™ Cold Plunge for many years to come.

Safety Precautions

Always disconnect power before servicing or performing maintenance on the chiller.

Do not tip, tilt, or invert the chiller. If the unit is moved out of an upright position, allow it to stand upright for a minimum of 24 hours before restoring power.

Maintain adequate airflow around the chiller. Provide at least 4 feet of clearance at the access panel and 3 feet of clearance at the rear of the unit.

When the cold plunge is not in use, keep it covered to help maintain water temperature, reduce energy consumption, and limit debris.

If ambient temperatures fall to 32°F (0°C) or below, shut off and fully drain the chiller to prevent freeze-related damage.

See more safety instructions below.

Included Components

- Pre-installed chiller
- Digital touch display
- Camlock quick-connect fittings
- Pentair® Pentek® 5" sediment filter
- UV clarifier

All components are pre-installed for straightforward startup.

Before first use, place the Cedro Sauna™ Cold Plunge on a flat, stable surface with proper airflow around the chiller vents.

Chiller Removal (If Required)

Unplug the chiller before removal.

Photograph the display wiring for reference.

Disconnect the chiller from the touch display.

Release both camlock fittings; use a towel and container if residual water is present.

Keep the chiller upright at all times; if tilted or inverted, wait 24 hours before restoring power.

Key Step in Set Up

Water Filling

Fill the tub before plugging in the chiller; the pump is not self-priming.

Locate the two circulation ports. The *intake port* is at the bottom of the tub and is responsible for bringing water to the chiller. The *supply port* is at the top of the tub and this port moves the clean chilled water.

Fill the tub with water until it is filled above the intake port.

Then, use a hose to fill the tub through the intake port until water flows from the supply port.

Once water flows from the supply port, plug in the chiller.

Do not fill more than three inches above the supply port.

Operation

Temperature Control

Press Set on the digital display.

Use the up or down arrows to select the desired temperature.

The system will automatically maintain the selected setting.

Normal Operation

Condensation on filters and hoses is normal.

The cabinet is designed to manage and disperse moisture.

Maintenance & Care

Sediment Filter

Inspect the Pentair® Pentek® 5" sediment filter monthly.

Clean or replace as needed.

UV Clarifier

Check the UV bulb annually to confirm proper operation.
Replace if necessary.

Winterization

If ambient temperatures are expected to reach 32°F (0°C) or below, power off, drain, and remove the chiller to prevent freeze damage.

Use Without Chiller

Caps are included for operating the cold plunge without the chiller installed.

Technical Specifications

Power: 110–120V / 4 amps

Safety

IMPORTANT SAFETY INSTRUCTIONS.

READ AND FOLLOW ALL INSTRUCTIONS.

When using electrical equipment, basic safety precautions must always be followed, including the following. Failure to follow these instructions may result in property damage, serious injury, electric shock, drowning, hypothermia, or death.

SIGNAL WORD DEFINITIONS

DANGER indicates an imminently hazardous situation which, if not avoided, will result in death or serious injury.

WARNING indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.

CAUTION indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury or equipment damage.

ELECTRICAL SAFETY

DANGER — RISK OF ELECTRIC SHOCK

- This appliance must be grounded. In the event of a malfunction or breakdown, grounding reduces the risk of electric shock by providing a path of least resistance for electric current.
- Connect only to a properly grounded, GFCI-protected receptacle. Do not remove the grounding pin from the plug.
- All electrical connections must comply with local, state, and national electrical codes and be performed by a licensed electrician.
- Do not energize the unit until it is filled to the minimum required water level. Operating the pump without water will cause damage and void the warranty.
- Never bypass, remove, or disable any Ground Fault Circuit Interrupter (GFCI). Doing so creates an unsafe condition and voids the warranty.
- Keep all electrical appliances, including but not limited to lights, telephones, radios, televisions, and similar devices, at least 1.5 m (5 ft) away from the unit.
- Install the unit a minimum of 1.5 m (5 ft) from all electrical equipment.

WARNING

- Always disconnect power before installing, removing, or servicing any component.
- Inspect all power cords, plugs, and electrical components before use. Do not operate if damaged.
- Provide a drip loop in the power cord to prevent water from traveling toward the electrical outlet.
- Do not use extension cords unless absolutely necessary. If used, the extension cord

must be properly rated for the electrical load.

- Do not immerse plugs or electrical components in water or operate the unit with wet hands or wet plugs.
- Close supervision is required when this product is used near children.

UV SYSTEM SAFETY (IF EQUIPPED)

DANGER

- Inspect the quartz sleeve and UV-C lamp prior to installation. Do not operate if damaged.
- Do not operate the UV system if water is present on components not intended to be wet.
- If the UV unit falls into water, do not reach into the water. Disconnect power before retrieval.
- Avoid exposure to UV radiation. UV light can cause severe eye and skin injury.
- The UV system is not intended for swimming pools or applications involving bodily contact with water.
- The UV system is not submersible and must never be submerged.

CHILD SAFETY

DANGER — RISK OF DROWNING

- Children must not use this product without constant adult supervision.
- Prevent unauthorized access by children at all times.
- Never operate the unit if suction fittings are broken, loose, or missing.
- Replacement pumps or fittings must match original flow specifications.

HEALTH & OPERATIONAL WARNINGS

WARNING

- Prolonged immersion in cold water may result in hypothermia, which can be fatal.
- Do not use this product while under the influence of alcohol, drugs, or medications that may cause drowsiness or impair judgment.
- Individuals who are pregnant or may be pregnant should consult a physician before use.
- Persons with heart disease, high or low blood pressure, circulatory disorders, diabetes, obesity, or those taking medication should consult a physician before use.
- Persons with infectious diseases should not use this product.
- Exercise caution when entering or exiting the unit to prevent slips or falls.
- Always verify water temperature using an accurate thermometer before use.

EQUIPMENT & ENVIRONMENTAL CAUTIONS

CAUTION

- Do not operate the unit without adequate water flow.
- Do not operate in freezing conditions. Drain and store the unit in a protected location.
- Do not place the unit in direct sunlight or near flammable materials.
- Do not exceed the maximum pump flow rate specified by the manufacturer. Operating beyond specifications may result in equipment damage and void the warranty.
- This unit is not submersible.

INSTALLATION & STRUCTURAL SAFETY

WARNING

- Above-ground installation is recommended.
- The unit must be installed on a solid, level foundation capable of supporting the filled weight of the unit.
- For deck installations, consult a qualified contractor or structural engineer to verify load capacity.
- The filled unit weighs approximately 2,000 lbs (907 kg). Structural failure may occur if weight limits are exceeded.

Warranty

LIMITED WARRANTY — RESIDENTIAL USE ONLY

Cedro Cold Plunge (“Manufacturer”) warrants to the original residential purchaser (“Owner”) that the Cedro Cold Plunge unit (“Product”) shall be free from defects in materials and workmanship under normal residential use and service for a period of one (1) year from the original date of purchase, subject to the terms, conditions, and exclusions set forth herein.

1. SCOPE OF WARRANTY COVERAGE

During the applicable warranty period, the Manufacturer warrants the following factory-installed components:

1.1 Vessel and Structural Components

- The stainless steel vessel is warranted against water loss resulting from defects in materials or workmanship for one (1) year from the original date of purchase.

1.2 Mechanical and Electrical Equipment

- Pumps, heaters (if equipped), and control systems are warranted against malfunction due to defects in materials or workmanship for one (1) year from the original date of purchase.

1.3 Plumbing and Water Treatment Components

- Plumbing components are warranted against leakage caused by defects in materials or workmanship for one (1) year from the original date of purchase.
- The factory-installed water purification system is warranted against malfunction due to defects in materials or workmanship for one (1) year from the original date of purchase.
- UV-C lamps and quartz sleeves are warranted for ninety (90) days from the original date of purchase.

1.4 Other Factory-Installed Components

- All other factory-installed components not specifically excluded herein, including but not limited to frames, valves, lighting systems, filter housings, lids, and mechanical assemblies, are warranted against malfunction due to defects in materials or workmanship for one (1) year from the original date of purchase.

2. WARRANTY EXCLUSIONS AND VOID CONDITIONS

This Limited Warranty shall be void if the Manufacturer or its authorized representative determines that the Product has been subjected to any of the following:

- Use in commercial, institutional, or non-residential applications

- Alteration, modification, neglect, misuse, abuse, or improper installation
- Failure to install, operate, or maintain the Product in accordance with the Owner's Manual
- Improper or unbalanced water chemistry
- Use of abrasive, corrosive, or non-approved cleaning agents
- Installation or use of non-genuine or aftermarket parts or accessories, including but not limited to filters, UV-C lamps, repair components, or accessories
- Repairs or service performed by any party other than the Manufacturer or an authorized service representative
- Damage caused by accident, acts of God, fire, flood, freezing, or other causes beyond the Manufacturer's control
- Freight damage incurred during transportation by a common carrier

This Limited Warranty does not cover:

- Insulating covers
- Consumable components except as expressly stated
- Any component added or installed after the date of manufacture
- Costs associated with gaining access to components for repair or replacement
- Products installed or serviced outside the contiguous United States

3. WARRANTY SERVICE AND REMEDY

To obtain warranty service, the Owner shall:

1. Notify the Manufacturer promptly upon discovery of a defect
2. Provide proof of original purchase
3. Take reasonable steps to prevent further damage to the Product

At its sole discretion, the Manufacturer shall repair or replace any component determined to be defective under this Limited Warranty. Replacement components or units shall be of equal value and functionality.

The Manufacturer shall not be responsible for:

- Providing access to the Product
- Removal or reinstallation of the Product
- Travel, transportation, or mileage charges
- Shipping or handling costs associated with replacement units

Any replacement Product shall carry only the remaining portion of the original warranty period.

4. LIMITATION OF IMPLIED WARRANTIES

To the extent permitted by applicable law, this Limited Warranty is in lieu of all other warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose.

No dealer, distributor, installer, service provider, or other third party is authorized to modify, extend, or alter the terms of this Limited Warranty.

5. LIMITATION OF LIABILITY

To the maximum extent permitted by law, the Manufacturer shall not be liable for any incidental, consequential, indirect, or special damages, including but not limited to loss of use, water damage, property damage, or removal costs, arising out of or related to any defect in the Product.

The Manufacturer's total liability under this Limited Warranty shall not exceed the original purchase price paid for the Product.

6. GOVERNING LAW AND LEGAL RIGHTS

This Limited Warranty gives the Owner specific legal rights. The Owner may also have other rights that vary by jurisdiction. Some jurisdictions do not allow limitations on implied warranties or the exclusion of incidental or consequential damages; therefore, certain limitations contained herein may not apply.

7. WARRANTY SERVICE AUTHORIZATION

All warranty service must be performed by the Manufacturer or its authorized service representative using approved replacement parts.