

Wood burning heater Harvia Pro 20 LS black

WKPR20LSM

The Harvia 20 LS Pro heater is a popular choice for cottage saunas thanks to its practicality. The left side of the heater features a fixed and easy-to-use 30-litre water tank that heats up the water while the heater is being heated for bathing.

Advantages

- Harvia Pro 20 LS with a side water tank is a practical wood-burning heater that gives excellent sauna experience
- Water tank on the left side of the heater, where the water is heated in the spacious 30 litre tank at the same time as the heater heats up the sauna to the desired temperature
- Easy and safe to use, , the tap for the water tank is located at the front of the heater
- The front, top and ash box are made of stainless steel, which is easy to keep clean
- The cast-iron glass hatch adds light and cozy atmosphere to the sauna



Features

Main material : Steel

H x W x D : 740.0 x 585.0 x 510.0 mm

Net weight (kg) : 60.0

Stone amount (kg) : 40.0

ID	GTIN	Power	Sauna room size min - max m3
WKPR20LSM	6417659036566	24.1 kW	8.0-20.0



Spare parts

Product	ID	Pcs
Casing, Harvia 20 LS	WX059	1
Handle and screws, Chrome	SPZKIP-670	1
Adjustable legs for LG150/SL	SPZKIP-918	1
Nut R1/2 25mm	SPZES-250	1
Hinge pin	SPZKIP-50	1
Water container, 20 Pro RS/LS	SP520	1
Extension 25 mm hot water faucet	SPZES-240	1
Connection pipe 200 mm	SPZKIP-130	1
Glass 184x210x4 mm Stoves 2006-, transparent	SPZTS-36	1
Tab hot water container, Chrome	SPZVS-100	1
Gasket for hot water faucet	SPZES-260	1
Stove door with glass (from 2006)	SP048	1
Cast-iron grating 135x290mm, sauna heaters	SPZKIP-10	1
22LS/RS lid, assembled	SPZR0ST-619	1
Flue pipe connector	SPZR0B-200	1
Cap for smoke hole (Ø 75 mm)	SPZR0B-430	1
Ashtray black, sauna heaters	SP682	1
Blocking plug with screws	SPZR0B-190	1
Flue gas heat regulator 2 pcs	SP0009	1

Technical details

Technical data	Type / attribute	WKPR20LSM
	Color	Black
	Power output	24.1 kW
	Stone sizes	Ø10-15 cm
	Stone amount (kg)	40
Dimensions	Product width	585
	Product height	740
	Product depth (mm)	510
	Net weight (kg)	60
	Gross weight	63.1
	Package width	660
	Package height	760
	Package depth	550
Connections	Flue connection locations	Back, Top
	Chimney connection diameter	115
Safety and installation dimensions	Safety distance front (non-combustible materials)	300
	Safety distance front (combustible materials)	300
	Safety distance right side (combustible materials)	300
	Safety distance right side non-combustible materials	100
	Safety distance left side (combustible materials)	300
	Safety distance left side non-combustible materials	100
	Safety distance behind (non-combustible materials)	100
	Safety distance behind (combustible materials)	300



Technical details

Technical data	Type / attribute	WKPR20LSM
	Safety distance (Ceiling)	1300
	Room min. height(depends on connections and therefore from output, star/delta)	2060